

## FORTUS AM40



Designed for tough environments like DIY-stores and supermarkets, yet still with class and style. Meet the FORTUS AM40.

Besides an advanced article surveillance system offering the best possible detection performance, FORTUS AM40 also features integrated visitor counting, jammer detection and advertising possibilities.

All systems from the FORTUS AM series offer remote connectivity, which enables direct insight in store and system performance. Automatically generated reports can be sent to your mailbox and information can be easily integrated into existing management information systems.

Remote maintenance guarantees optimum operation at minimum cost.

The FORTUS AM40 has a reinforced base-frame and can be supplied with a normal base plate with two mounting holes or with an XL base plate with four additional mounting holes, which will ensure proper fixation to any floor type. The choice is yours.

### Unique features

---

Premium detection combined with maximum transparency

---

Selectable notifications for different alarm types

---

Remote service enabled, management information available

---

Integrated visitor counters and multi-color alarm lights


---

Selectable base plate

---

Also available in RF

---



## FORTUS AM Antenna Line

Features	MONO	DUAL
	FORTUS AM40	FORTUS AM40
Anodized aluminum with transparent panels	●	●
Premium detection	●	●
Remote service and management information <sup>1</sup>	●	●
Selectable notifications for all alarm types	●	●
Multi-color alarm lights	●	●
Integrated bi-directional visitor counter <sup>1</sup>	●	●
Distinction between in- and outgoing alarms	-	●
Integrated metal detection	-	○
Jammer detection	●	●
Aisle light-up during alarm (both antennas)	●	●
Advertising panels	○	○

### Detection distance <sup>2</sup>

Cross Point OSTRAL F25 hard tag (Ø 25 mm)	up to 1.3 m	up to 2.7 m
Cross Point OSTRAL D55 hard tag (Ø 55 mm)	up to 1.3 m	up to 2.7 m
DR label	up to 1.0 m	up to 2.1 m

### Specifications


Width / height / depth	380 mm / 1587 mm / 53 mm	
Weight	10 kg	
Operating frequency	58 kHz	
Power supply (external, TRX only)	Input: 115/230VAC 50-60Hz, output: 32.5VDC + sync	
Power over field bus (receivers only)	●	
Ambient temperature	0°C to 50°C	
Relative humidity	0% to 90%, non-condensing	
Programmable I/Os	2	

### Base plates <sup>3</sup>

Depending on the floor type where the FORTUS AM40 is installed, the following base plates are available:



Normal base plate with two mounting holes (382 x 56 mm)



XL base plate with four additional mounting holes (416 x 100 mm)

● standard available

○ optional

- not available

<sup>1</sup> In combination with the CrossCONNECT Access Point  
<sup>2</sup> Tested with Cross Point tags in all orientations, depending on environment. For mono the specified distance is on each side of the antenna.

<sup>3</sup> Antennas are supplied with normal base plates. The XL base plate is optionally available and needs to be ordered separately.